

OH02B20

2-megapixel product brief

1/7.5" CMOS 2-Megapixel (1500 x 1500) Image Sensor with PureCel®Plus-S Technology

OH02B20 is a square 2-megapixel (MP) (1500 x 1500) resolution CMOS image sensor for gastrointestinal, ENT, orthopedic, surgical, dental, and veterinarian reusable and disposable endoscopes, catheters, and guide wires. The miniature square form factor of the OH02B20 saves space for higher resolution in smaller designs. It allows endoscopes to have a smaller outer diameter (6 mm) or larger working channels for advanced endoscope designs. The OH02B20 is based on OMNIVISION's latest PureCel®Plus-S stacked-die technology, enabling high functionality in the smallest possible die size.

The OH02B20 is autoclavable and does not require tuning or calibration.

Find out more at www.ovt.com.







Ordering Information

OH02B20-A24A-001A-Z (color, lead-free)

Applications

endoscopes

Technical Specifications

- active array size: 1516 x 1516
- maximum image transfer rate:
- 1500 x 1500: 60 fps
- power requirements: standby: 650 µA
- output formats: 10-bit RGB RAW
- lens size: 1/7.5"
- lens chief ray angle: 15° non-linear

- temperature range:
- operating: -30°C to +85°C junction temperature
- stable image: 0°C to +60°C junction temperature
- scan mode: progressive
- pixel size: 1.116 μm x 1.116 μm
- image area: 1691.856 μm x 1691.856 μm
- CSP with SAR 2.5 mm x 2.5 mm

Product Features

- automatic black level calibration (ABLC)
 supports typical images sizes:
- programmable controls for:
- frame rate
- mirror and flip
- binning
- cropping
- windowing
- support for dynamic DPC
- supports output formats: - 10-bit RGB non-HDR
- supports horizontal and vertical subsampling

- 1500 x 1500
- 1280 x 720
- 960 x 540 - 640 x 480
- AntLinx™ (4-wire) interface with speeds up to 1.6 Gbps
- standard serial SCCB interface
- HDR support:
- stagger HDR 2 exposure timing
- two on-chip phase lock loops (PLLs)
- built-in temperature sensor
- 1.116 μm x 1.116 μm pixel

Functional Block Diagram







