



OV9750

720p product brief



High Performance 1/3-Inch Image Sensor Brings 720p HD Video to Mainstream Surveillance Camera Applications

OMNIVISION's new OV9750 is a high performance 1/3-inch 720p high definition (HD) sensor designed specifically for mainstream consumer and commercial security systems. The sensor utilizes OMNIVISION's latest OmniPixel®3-HS with dual conversion gain frontside illumination technology to capture high definition (HD) video used for popular analog 960H CCTVs, as well as HD analog and 720 HD network cameras. The OV9750 also has high near-infrared (NIR) sensitivity for day and night camera applications.

Built on 3.75-micron OmniPixel®3-HS with dual conversion gain pixel architecture, the OV9750 achieves excellent image performance, enabling clear image and video recording in both high- and low-light environments. The OV9750 is capable of operating in SXGA (1280 x 960) resolution at 60 frames per second (fps) with 10-bit output, or at 45 fps with 12-bit output.

Additionally, the sensor fits into a 6.3 mm x 5.2 mm package and supports ultra-low power mode (ULPM), which reduces resolution and frame rates to conserve additional power for very low-power camera design.

Find out more at www.ovt.com.



- OV9750-H55A (color, lead-free)
55-pin CSP

Applications

- security and surveillance cameras
- PC multimedia
- wearables
- 960H for analog CCTV applications

Technical Specifications

- active array size:** 1280 x 960
- maximum image transfer rate:**
 - SXGA (1280 x 960): 60 fps
 - 720p (1280 x 720): 60 fps
 - VGA (640 x 480): 120 fps
- power supply:**
 - analog: 3.15V to 3.45V (3.3V nominal)
 - core: 1.7V to 1.9V (1.8V nominal)
 - I/O: 1.7V to 1.9V (1.8V nominal)
- power requirements:**
 - active: 166 mW
 - standby: 51 μ W
 - XSHUTDN: 13 μ W
- temperature range:**
 - operating: -30°C to +85°C junction temperature
 - stable image: 0°C to +60°C junction temperature
- output interface:** 2-lane MIPI/LVDS serial output/DVP parallel output
- output formats:** 10/12-bit RGB RAW
- lens size:** 1/3"
- lens chief ray angle:** 9° linear
- pixel size:** 3.75 μ m x 3.75 μ m
- image area:** 4860 μ m x 3660 μ m

Product Features

- 3.75 μ m x 3.75 μ m pixel
- 1280 x 960 at 60 fps @ 10-bit, 45 fps @ 12-bit
- programmable controls for:
 - frame rate
 - mirror and flip
 - cropping
 - windowing
- supports images sizes:
 - SXGA (1280 x 960)
 - 720p (1280 x 720)
 - VGA (640 x 480), and more
- 58 bytes of embedded one-time programmable (OTP) memory for customer use
- ultra low power mode (ULPM)
- support for output formats: 10/12-bit RGB RAW
- two-wire serial bus control (SCCB)
- MIPI/LVDS serial output interface (1- or 2-lane)/DVP interface
- 2x binning support
- image quality control:
 - defect pixel correction
 - automatic black level calibration

Functional Block Diagram

