


# OV493

## ASIC product brief



### Cost-Effective Surround-View Image Processing Solution for Automotive Applications

OMNIVISION's OV493 is a compact image signal processor (ISP) companion chip that brings best-in-class image quality to 360-degree surround-view and video mirror imaging applications. By processing two video streams simultaneously, the OV493 makes it possible for a system with only two ISP companion chips to process four camera inputs, enabling flexible electronic control unit (ECU) designs for surround-view applications and dramatically reducing overall system cost.

While most ISP companion chips are located on the camera module, the OV493 can be placed on the ECU module for unprecedented flexibility and streamlined system architectures. The OV493 is designed to work seamlessly with OMNIVISION's high-performance OV9716 and OV10640 automotive image sensors, supporting dual sensor input of up to 1.4-megapixels at 30 frames per second (fps) with high dynamic range (HDR) each.

The OV493 comes in an AEC-Q100 Grade 2 qualified 7 x 7 mm ball grid array (BGA) package.

Find out more at [www.ovt.com](http://www.ovt.com).



- **OV00493-B69G-1B** (lead-free)  
169-pin BGA, packed in tray
- **OV00493-B69G-TB** (lead-free)  
169-pin BGA, packed in tape and reel

## Applications

- surround view systems
- camera monitoring systems (CMS)
- e-mirrors

## Technical Specifications

- **power supply:**
  - core: 1.1V -5% ~ 1.1V +10%
  - I/O: 1.8V ±5% or 3.3V ±5%
- **power requirements:** 265 mW, measured at 1392 x 976 @ 30 fps, 12-bit plus 12-bit input from OV9716 via MIPI interface and 1392 x 976 YUV422 output via MIPI interface
- **temperature range:**
  - operating: -40°C to +105°C ambient temperature and -40°C to +125°C junction temperature
- **package dimensions:** 7 mm x 7 mm

## Product Features

- AEC-Q100 grade 2 qualified
- advanced 100 Mp/s throughput ISP for high quality image capturing and video streaming
- local and global tone mapping support
- up to 3-capture HDR combination
- simultaneous output of fully processed YUV for display-based applications and RAW for machine vision applications
- embedded information including frame counter, temperature, and register data for each image to enable critical automotive safety applications
- auto white balance (AWB)
- automatic exposure control (AEC) / automatic gain control (AGC)
- supports statistics data of up to four user programmable ROIs
- SCCB master/slave interface for sensor and ASIC configuration
- supports four-wire or two-wire serial interface to retrieve stored firmware from external memory devices, such as EEPROM
- on-chip PLL to generate internal clocks
- on-chip voltage regulator 1.8V to 1.1V
- brown-out detection circuit and output flag
- supports 2x2 lane MIPI RX/TX and 1x4 lane MIPI RX/TX
- supports 12-bit DVP input, shared with MIPI RX (1.0 Gbps/lane)
- supports 12-bit DVP output, shared with MIPI TX
- supports 24-bit DVP output, shared with BT1120 output
- embedded 32-bit RISC processor for high performance and flexibility
- supports 1K bits of one-time programmable memory (OTP)
- JTAG boundary scan

## Functional Block Diagram

